



MODEL 25MF

Durable 25 lb. unit for economical, accurate measuring. Approved flow meter. Built-in air release. Measures grease in pints or ½ pints. 5½' grease hose. Type "C" nozzle. Oval type tapered container with fill opening. Mounted on four-leg malleable iron base. Shipping weight approx. 34 lbs.

MODEL 25MCF Same as Model 25MF except includes built-in counter or "totalizer." Shipping weight approx. 34 lbs.



MODEL 25ML

MODEL 25 An inexpensive 25 lb. BENNETT Grease unit. Same as Model 25MF without meter. (Not approved in states requiring special metering equipment.) Shipping weight approx. 27 lbs.

MODEL 25M Similar to Model 25 but equipped with a mechanical type meter. Shipping weight approx. 30 lbs.

MODEL 25MC Same as Model 25M but equipped with totalizing register. Shipping weight approx. 32 lbs.

NOTE: Models 25M and 25MC—not approved in states requiring metered grease dispensers.


MODEL 25ML Basically a Model 25 with approved mechanical type meter and automatic float type lock. Shipping weight approx. 33 lbs.

MODEL 25MCL Same as Model 25ML but equipped with totalizing register. Shipping weight approx. 33 lbs.




MODEL 651

Barrel Grease Pump—one pint self-measuring. Fitted with special bung bushing for 2" drum opening. Intake adjustable to fit 15 to 65-gallon drums. Enclosed steel rack and pinion with overhead discharge. 5½' grease hose. Type "C" nozzle. Shipping weight approx. 27 lbs.



TRU-LOC BAND

Provides by far the simplest method of installing bed-plate on 25 and 100-pound round containers. Affords a positive seal, can be locked in the closed position. Easy to remove when container needs refilling.



FLOAT TYPE AUTOMATIC LOCK
On ML Models. Float lowers as grease is used, automatically engaging clutch on pinion shaft, preventing handle from turning.



TYPE A "SOLO" NOZZLE
Manually operated valve and latch to hold in open position. Spring actuated valve in tip. (Supplied for all Bennett grease dispensers at slight additional cost.)



AIR RELEASE

On MF Models—by-passes air and allows only grease to pass through the meter.



TYPE C "SOLO" NOZZLE

One-piece steel tube construction with sealed-in ball assembly. Ball stop prevents ball from seating in outlet opening. (Standard on all Bennett Grease Dispensers.)



MODEL 3 TRUCK

Sturdy, triangle with two front wheels 3¾" diameter and 1½" face. Rear wheel 8½" diameter and 1½" face. Barrel clamp for locking 30 to 60-gallon drums on truck. Shipping weight approx. 30 lbs.



MODEL 2 TRUCK

For standard 100-lb. drums. Two 7" wheels, with 1½" tread. Shipping weight approx. 18 lbs. All 100-lb. outfits with suffix "B" furnished less trucks.